


防水工业插头插座

Waterproof industrial plug and socket




- IP 67 法兰尺寸75×75毫米(16A), 85×75毫米(32A),直插式,附加插座
- IP 67 软接触工艺,法兰尺寸107×100毫米,直插式,附加插座
- IP 67 法兰尺寸65×65毫米(16A), 安装尺寸52×52毫米(一体式) 尺寸图: D005

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
16	3	217	218	219			
16	4	220	221	222	223	224	225
16	5	226	227	228			
32	3	229	230	231			
32	4	232	233	234	235	236	237
32	5	238	239	240			
63	3	1263	1264	1265			
63	4	1122	1123	1124	1125		
63	5	1126	1127	1128			
16	3	MXS-B1365-4	MXS-B1365-6	MXS-B1365-9			
16	4	MXS-B1465-4	MXS-B1465-9	MXS-B1465-6			




- IP 67 笼式弹簧接触工艺,法兰尺寸130×130毫米,直插式,附件插座 尺寸图: D006

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
125	3		3380				
125	4	1455	1456	1457	1458		
125	5	1459	1460	1461	3283		



- IP 67 法兰尺寸73.5×64毫米,(16 A,3极) 100×92毫米,内向倾斜20° 附加插座
- IP 67 软接触工艺,法兰尺寸110×106毫米,内向倾斜20°,附加插座 尺寸图: D007

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
16	3	1474	1475	1476			
16	4	1477	1478	1479	1480	1481	1482
16	5	1483	1484	1485			
32	3	1501	1502	1503			
32	4	1504	1505	1506	1507	1567	1568
32	5	1489	1490	1551			
63	3	2179	2180	2181			
63	4	203	204	205	206		
63	5	207	208	209	3507		




- IP 67 笼式弹簧接触工艺,法兰尺寸114×110毫米,内向倾斜15° 附加插座 尺寸图: D008

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
125	3		3575				
125	4	210	211	212	213		
125	5	214	215	216			



- IP 67 CEE/IEC插头,带螺钉接线端子,一体外壳结构 尺寸图: A004

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
16	3	277	278	279			
16	4	280	281	282	283	284	285
16	5	286	287	288			
32	3	289	290	291			
32	4	292	293	294	295	296	297
32	5	298	299	300			



- IP 67 CEE/IEC插头,带外部电缆紧固装置及耐热接触载体,插销表面镀镍 尺寸图: A006

A	P	110V	230V	400V	500V	>50-500V	
		50 a. 60Hz 3P 4P 5P 4H 4H 4H	50 a. 60Hz 3P 4P 5P 6H 9H 9H	50 a. 60Hz 3P 4P 5P 9H 6H 6H	50 a. 60Hz 3P 4P 5P 7H 7H 7H	100-300Hz 3P 4P 5P 10H 10H 10H	300-500Hz 3P 4P 5P 2H 2H 2H
63	3	1570	1571	1572			
63	4	1108	1109	1110	1111		
63	5	1112	1113	1114	2958		
125	3	3399	3400				
125	4	1441	1442	1443	1444		
125	5	1445	1446	1447	3173		